



DECLARATION OF CONFORMITY

The undersigned, representing

Stenvalls Trä AB

and manufacturing plant

Luleå, Sweden

herewith declares that the

Sawn, planed or profiled panelling and cladding with or without tongue and groove with characteristics and performance declarations as below

Characteristic

Performance declaration

Intended use	Internal or external panelling/cladding for wall or ceiling
Species/species group	WPPA: spruce (<i>Picea abies</i>) and pine (<i>Pinus sylvestris</i>)
Growth area	NNE Europe (Northern and North Eastern Europe)
Minimum thickness	6 mm
Reaction to fire	D-s2, d2 (CWFT – EN 14915, Table 1; density 390 kg/m ³ ; minimum total thickness 9 mm, minimum thickness 6 mm)
Formaldehyde class	E1
Content of pentachlorophenol	None
Water vapour permeability	60 (see EN 14915, clause 5.4)
Sound absorption coefficient	0,10/0,30 (see EN 14915, clause 5.5)
Thermal conductivity	0,11 (see EN 14915, clause 5.6)
Natural durability class	4 (EN 350-2)

is in conformity with the provisions of the EC Directive 89/106/CEE (Construction Products Directive - CPD) and that Annex ZA of

EN 14915:2006

has been applied.

The CE marking was affixed in 2008.

Name and address of the company:

Stenvalls Trä AB
Vargbackevägen 1
942 94 Sikfors
SWEDEN

Luleå, 25th of June 2008


Anders Nilsson, Branch manager